

Safety Data Sheet **PETROLEUM SPIRIT 60-80°C AR**

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

SECTION 1: Identification

GHS Product identifier

Product name PETROLEUM SPIRIT 60-80°C AR

Product number PA210

Recommended use of the chemical and restrictions on use

Solvent.

Supplier's details

Name ChemSupply Australia Pty Ltd
Address 38-50 Bedford Street
5013 Gillman South Australia
Australia

Telephone 08 8440 2000
email www.chemsupply.com.au

Emergency phone number

CHEMCALL 1800 127 406 (Australia) / +64-4-917-9888 (International)

SECTION 2: Hazard identification

General hazard statement

Dangerous goods of Class 3 (Flammable Liquid) are incompatible in a placard load with any of the following: Class 1, Class 2.1, if both the Class 3 and Class 2.1 dangerous goods are in bulk, Class 2.3, Class 4.2, Class 5, Class 6, if the Class 3 dangerous goods are nitromethane, Class 7.

Classified as dangerous goods according to the Australian Dangerous Goods Code (ADG).

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classification of the substance or mixture

GHS classification in accordance with: UN GHS revision 7

- Skin corrosion/irritation, Cat. 2
- Specific target organ toxicity following repeated exposure, Cat. 2
- Specific target organ toxicity following single exposure, Cat. 3
- Toxic to reproduction, Cat. 2
- Hazardous to the aquatic environment, long-term (chronic), Cat. 2
- Aspiration hazard, Cat. 1
- Flammable liquids, Cat. 2

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

GHS label elements, including precautionary statements

Pictograms



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapor

H304

May be fatal if swallowed and enters airways

H315

Causes skin irritation

H336

May cause drowsiness or dizziness

H361

Suspected of damaging fertility or the unborn child

H373

May cause damage to organs through prolonged or repeated exposure

H411

Toxic to aquatic life with long lasting effects

Precautionary statement(s)

P202

Do not handle until all safety precautions have been read and understood.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P240

Ground and bond container and receiving equipment.

P241

Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242

Use non-sparking tools.

P243

Take action to prevent static discharges.

P260

Do not breathe dust/fume/gas/mist/vapors/spray.

P261

Avoid breathing dust/fume/gas/mist/vapors/spray.

P264

Wash hands thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician

P302+P352

IF ON SKIN: Wash with plenty of water/soap

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313

IF exposed or concerned: Get medical advice/attention.

P312

Call a POISON CENTER/doctor/physician if you feel unwell.

P314

Get medical advice/attention if you feel unwell.

P331

Do NOT induce vomiting.

P332+P313

If skin irritation occurs: Get medical advice/attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

P370+P378

In case of fire: Use agents recommended in Section 5 of SDS for extinction

P391

Collect spillage.

P403+P235

Store in a well-ventilated place. Keep cool.

P501

Dispose of contents/container to an approved waste disposal facility

SECTION 3: Composition/information on ingredients

Mixtures

Mixture of Hydrocarbons

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

Component	Identification	Weight %
N-hexane	CAS no.: 110-54-3 EC no.: 203-777-6 Index no.: 601-037-00-0	50 - 100 %
Hydrocarbons, c6-c7, isoalkanes, cyclics, <5% n-hexane	EC no.: 926-605-8	5 - 10 %
Hydrocarbons, c6, isoalkanes, <5% n-hexane	EC no.: 931-254-9	5 - 10 %

SECTION 4: First-aid measures

Description of necessary first-aid measures

General advice

First Aid Facilities: Maintain eyewash fountain and drench facilities in work area.

Advice to Doctor: Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

If inhaled

If inhaled, remove from contaminated area to fresh air immediately, avoid becoming a casualty. Make patient comfortable, keep warm and at rest until fully recovered. If breathing is difficult (or develops a bluish skin discolouration), supply oxygen by a qualified person. Apply artificial respiration with a respiratory medical device if not breathing. Do not use mouth to mouth resuscitation. Immediately medical attention is required.

In case of skin contact

Immediately remove contaminated clothing and wash affected area with water for at least 15 minutes. Ensure contaminated clothing is washed before re-use. Seek medical advice / attention depending on the severity.

In case of eye contact

Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. In all cases of eye contamination it is a sensible precaution to seek medical advice.

If swallowed

Rinse mouth thoroughly with water immediately, repeat until all traces of product have been removed.
DO NOT INDUCE VOMITING. Seek immediate medical advice.

Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically based on judgement of doctor and individual reactions of the patient.

Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

For advice, contact the National Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Ensure medical personnel attending are aware of the identity and nature of the product(s) involved and take precautions to protect themselves.

SECTION 5: Fire-fighting measures

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

Suitable extinguishing media

Specific Methods: CAUTION: Use of water spray when fighting fire may be inefficient.

SMALL FIRE: Use foam, dry chemical, CO₂ or water spray.

LARGE FIRE: Use foam, fog or water spray - Do NOT use water jets.

If safe to do so, move undamaged containers from the fire area. Cool containers with flooding quantities of water until well after the fire is out. Avoid getting water inside the containers.

Specific hazards arising from the chemical

Hazards from Combustion Products: Oxides of carbon.

HIGHLY FLAMMABLE: These products have a low flash point. Will be easily ignited by heat, sparks or flames. Vapours will form explosive mixtures with air. Vapours will travel to source of ignition and flash back. Most vapours are heavier than air and will collect in low or confined areas (drains, basements, tanks). Many liquids are lighter than water. Containers may explode when heated. Fire will produce irritating, poisonous and/or corrosive gases. Vapours from run-off may create an explosion hazard.

Special protective actions for fire-fighters

SCBA and structural firefighter's uniform may provide limited protection. Fully encapsulating, gas-tight suits should be worn for maximum protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate the area of all non-essential personnel. Avoid inhalation, contact with skin, eyes and clothing.

Remove ignition sources. Ventilate contaminated area thoroughly. Extinguish naked flames.

Use personal protective equipment listed in Section 8.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flame) within at least 50m. All equipment in handling this product must be earthed. Do NOT touch or walk through this product. Stop leak if safe to do so. Prevent entry into waterways, drains, confined areas.

Vapour suppressing foam may be used to control vapours. Water spray may be used to knock down or divert vapours.

Absorb spill with earth, sand or other non-combustible material. Use clean, non-sparking tools to collect material and place it in loosely-covered metal or plastic containers for later disposal. Water spray may be used to knock down or divert vapour clouds.

SEEK EXPERT ADVICE ON HANDLING AND DISPOSAL.

SECTION 7: Handling and storage

Precautions for safe handling

Earth or bond all equipment. Avoid prolonged or repeated contact with skin, eyes and clothing. Do not breath fumes which may accumulate in the vapour head-space of containers. Ensure the appropriate personal protective equipment is used when handling this material. Use in well ventilated areas away from all ignition sources. In case of insufficient ventilation, wear suitable respiratory equipment. All electrical equipment must be flameproofed. Keep container tightly closed when not in use.

Conditions for safe storage, including any incompatibilities

Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidizing agents. Store in well ventilated area. Keep containers closed at all times.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 110-54-3

N-hexane

AU/SWA (Australia): 20 ppm; 72 mg/m³ TWA inhalation [Hexane (n-Hexane)]

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

The use of a face shield, chemical goggles or safety glasses with side shield protection as appropriate. Must comply with Australian Standards AS 1337 and be selected and used in accordance with AS 1336.

Skin protection

Clean impervious clothing should be worn. Clothing for protection against chemicals should comply with AS 3765 Clothing for Protection Against Hazardous Chemicals.

Body protection

Footwear: Safety boots in industrial situations is advisory, foot protection should comply with AS 2210, Occupational protective footwear - Guide to selection, care and use.

Body Protection: Clean clothing or protective clothing should be worn, preferably with an apron. Clothing for protection against chemicals should comply with AS 3765 Clothing for Protection Against Hazardous Chemicals.

Respiratory protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/ NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/ NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	Colourless liquid.
Color	No data available.
Odor	Characteristic.
Odor threshold	No data available.
Melting point/freezing point	No data available.
Boiling point or initial boiling point and boiling range	63 - 80°C
Flammability	Keep away from heat, sparks or naked flames. Use flameproof equipment and fittings to prevent flammability risk. Electrically link and ground metal containers for transfer of the product to prevent accumulation of static electricity. Ensure adequate venti
Lower and upper explosion limit/ flammability limit	Flammable Limits - Lower: 1.0 Vol% Flammable Limits - Upper: 7.4 Vol%
Flash point	-26°C
Explosive properties	No data available.
Auto-ignition temperature	No data available.

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

Decomposition temperature	No data available.
Oxidizing properties	No data available.
pH	No data available.
Kinematic viscosity	No data available.
Solubility	Solubility in Water: Insoluble.
Partition coefficient n-octanol/ water (log value)	No data available.
Vapor pressure	No data available.
Evaporation rate	No data available.
Density and/or relative density	Specific Gravity: 0.666
Relative vapor density	No data available.
Particle characteristics	No data available.

Supplemental information regarding physical hazard classes

No data available.

Further safety characteristics (supplemental)

No data available.

SECTION 10: Stability and reactivity

Reactivity

Stable under normal conditions of storage and handling.

Risk of ignition. Vapours may form explosive mixtures with air

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Hazardous Polymerization: Will not occur.

Vapours may form explosive mixture with air.

Conditions to avoid

Avoid storing in direct sunlight and avoid extremes of temperature.

Heat, flames and sparks.

Incompatible materials

Strong oxidising agents. Heat. Various plastics and rubber.

Hazardous decomposition products

Oxides of carbon.

SECTION 11: Toxicological information

Information on toxicological effects

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

Acute toxicity

Ingestion: Causes irritation to mucous membranes of the gastrointestinal tract. May cause headache, dizziness, nausea, drowsiness, irritation of the mouth, throat and digestive tract and lung damage. Aspiration of liquid into the lungs can cause bronchopneumonia, pulmonary edema, or chemical pneumonitis.

Inhalation: Causes irritation to the mucous membranes of the respiratory tract (nose, mouth, throat, lungs). Inhalation of vapours may cause dizziness, drowsiness, headache, nausea, weakness, CNS effects and unconsciousness. Aspiration of liquid into the lungs can cause bronchopneumonia or pulmonary edema.

Skin corrosion/irritation

May cause skin irritation, degreasing effect on the skin and possibly followed by secondary inflammation. May be absorbed through the skin with resultant toxic effects such as headache, dizziness and nausea.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Toxic to Reproduction: Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (STOT) - single exposure

Specific Target Organ Toxicity - Single Exposure Category 3 (respiratory tract irritation)

H336 May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

Specific Target Organ Toxicity - Repeated Exposure Category 2

H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration Hazard: Category 1

H304 May be fatal if swallowed and enters airways.

Additional information

Chronic Effects: Blood changes of significant nature have been reported when the aromatic content of hydrocarbon products has been high. Repeated or prolonged skin contact may cause chronic dermatitis.

Other Information: Toxicological Information

110-54-3 n-hexane

Oral LD50 16,000 mg/kg (rat) (OECD 401)

Dermal LD50 >3,350 mg/kg (rabbit) (OECD 402)

Inhalative LC50 /4 h 259.3 mg/L (rat) (OECD 403)

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Oral LD50 >16,750 mg/kg (rat) (OECD 401)

Dermal LD50 >3,350 mg/kg (rabbit) (OECD 402)

Inhalative LC50 /4 h 259.354 mg/L (rat) (OECD 403)

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral LD50 >5,840 mg/kg (rat) (OECD 401)

Dermal LD50 >2,920 mg/kg (rat) (OECD 402)

Inhalative LC50 /4 h >25.2 mg/L (rat) (OECD 403)

SECTION 12: Ecological information

Toxicity

Known Harmful Effects on the Environment: Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

H411 Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers.

Other disposal recommendations

Do not discharge this material into waterways, drains and sewers.

SECTION 14: Transport information

ADG (Road and Rail)

UN Number: 3295

Class: 3

Packing Group: II

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S. (Contains n-Hexane, C6 Isoalkanes)

Hazchem emergency action code (EAC)

3YE

IMDG

UN Number: 3295

Class: 3

Packing Group: II

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S. (Contains n-Hexane, C6 Isoalkanes)

IATA

UN Number: 3295

Class: 3

Packing Group: II

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S. (Contains n-Hexane, C6 Isoalkanes)

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

Australia SUSMP

Poison Schedule: S5

SECTION 16: Other information

Further information/disclaimer

ChemSupply Australia Pty Ltd does not warrant that this product is suitable for any use or purpose. The user must ascertain the suitability of the product before use or application intended purpose. Preliminary testing of the product before use or application is

Safety Data Sheet

PETROLEUM SPIRIT 60-80°C AR

SDS no. 0Q83BTGR • Version 1.0 • Date of issue: 2025-08-27

recommended. Any reliance or purported reliance upon ChemSupply Australia Pty Ltd with respect to any skill or judgement or advice in relation to the suitability of this product of any purpose is disclaimed. Except to the extent prohibited at law, any condition implied by any statute as to the merchantable quality of this product or fitness for any purpose is hereby excluded. This product is not sold by description. Where the provisions of Part V, Division 2 of the Trade Practices Act apply, the liability of ChemSupply Australia Pty Ltd is limited to the replacement of supply of equivalent goods or payment of the cost of replacing the goods or acquiring equivalent goods.

Preparation information

All information provided in this data sheet or by our technical representatives is compiled from the best knowledge available to us. However, since data, safety standards and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, we make no warranty either expressed or implied, with respect to the completeness or accuracy to the information contained herein. ChemSupply Australia Pty Ltd accepts no responsibility whatsoever for its accuracy or for any results that may be obtained by customers from using the data and disclaims all liability for reliance on information provided in this data sheet or by our technical representatives.

Standard for the Uniform Scheduling of Medicines and Poisons, Commonwealth of Australia

National Road Transport Commission, 'Australian Code for the Transport of Dangerous Goods by Road and Rail 7th. Ed.'

Safe Work Australia, 'National Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals', July 2020.

Safe Work Australia, 'National Guide for Classifying Hazardous Chemicals', July 2020.

Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants, December 2019

Safe Work Australia, Hazardous Chemical Information System (HCIS), hcis.safeworkaustralia.gov.au

IATA, Dangerous Goods Regulations (DGR)

IMO, International Maritime Dangerous Goods Code (IMDG)