

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|--------------|--|
| Product name | PETROLEUM ETHER 40-60 |
| CAS-No. | 64742-49-0 |
| Product code | AR1147, GP1147, LC1147, LC1305, LV1147, PC1147, RP1147 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|-----------------|--------------------------------------|
| Identified uses | Chemical for analysis and production |
|-----------------|--------------------------------------|

1.3 Details of the supplier of the safety data sheet

| | |
|------------------|---|
| Company | ChemSupply Australia Pty Ltd 38 - 50 Bedford Street, Gillman SA 5013 Australia |
| Telephone number | (08) 8440 2000 |
| Fax number | (08) 8440 2001 |

1.4 Emergency Telephone Number

| | |
|--------------------------------------|--------------------------|
| Emergency phone | |
| Monday - Friday 8:30am - 5:00pm ACST | (08) 8440 2000 |
| After hours: CHEMCALL | 1800127406 / +6449179888 |

1.5 Manufacturer

| | |
|---------|---|
| Company | RCI LABSCAN LIMITED. 24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand |
|---------|---|

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to WHS Regulations (Australia)

Flammable liquids (Category 2), H225
 Skin irritation (Category 2), H315
 Reproductive toxicity (Category 2), H361f
 Specific target organ toxicity - single exposure (Category 3), H336
 Specific target organ toxicity - repeated exposure, (Category 2), Inhalation, H373
 Aspiration hazard (Category 1), H304
 Chronic aquatic toxicity (Category 2), H411
 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Pictogram



Signal word

Danger

Hazard statement(s)

| | |
|-------|---|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361f | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure if inhaled. |

| | |
|----------------------------|--|
| H411 | Toxic to aquatic life with long lasting effects. |
| Precautionary statement(s) | |
| P203 | Obtain, read and follow all safety instructions before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground and bond container and receiving equipment. |
| P242 | Use non-sparking tools. |
| P243 | Take action to prevent static discharges. |
| P260 | Do not breathe fume/gas/mist/vapours/spray. |
| P264 | Wash hand thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301 + P316 | IF SWALLOWED: Get emergency medical help immediately. |
| P302 + P352 | IF ON SKIN: Wash with plenty water. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P318 | IF exposed or concerned: Get medical advice. |
| P319 | Get medical help if you feel unwell. |
| P331 | Do NOT induce vomiting. |
| P332 + P317 | If skin irritation occurs: Get medical help. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P391 | Collect spillage. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |

2.3 Other hazards None

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Mixture of aliphatic hydrocarbon (C5-C6)

Synonyms Petroleum benzine, Petroleum spirit.

| CAS-No | EC-No | EC-Index-No | Formula | Molecular Weight | Weight % |
|------------|-----------|--------------|---------|------------------|----------|
| 64742-49-0 | 265-151-9 | 649-328-00-1 | - | - | - |

Hazardous ingredients according to WHS Regulations (Australia)

| Component | Concentration | Classification |
|--|---------------|---|
| Mixture of aliphatic hydrocarbon (C5-C6) | | |
| CAS-No 64742-49-0 EC-No 265-151-9 EC-Index-No 649-328-00-1 | - | Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361f Specific target organ toxicity - single exposure (Category 3), H336 Specific target organ toxicity - repeated exposure, (Category 2), Inhalation, H373 Aspiration hazard (Category 1), H304 Chronic aquatic toxicity (Category 2), H411 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| | |
|----------------|---|
| General advice | Show this safety data sheet to the doctor in attendance. |
| Inhalation | Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. |
| Skin contact | Remove contaminated clothing and wash affected skin with soap and water. If signs of poisoning appear, treat as for inhalation. Wash contaminated clothing before reuse. |
| Eye contact | Contaminated combustible material, e.g. clothing ignites more readily and burns fiercely. If the substance has got into the eyes, immediately wash out with plenty of water at least 15 minutes. Obtain medical attention. |
| Ingestion | Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person. |

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing, avoid vomiting. Risk of aspiration. Keep airways free. In case of spontaneous vomiting: Risk of aspiration. Pulmonary failure possible.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical or foam. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Vapors may form explosive mixture with air at ambient temperature. Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Hazchem Code

3YE

5.5 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Remove all sources of ignition. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel or chemical absorbent pads). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see **Section 13**.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Exposure limit (Safe Work Australia)**

Not Available

8.2 Exposure controls**Appropriate engineering controls**

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE)**Eye/face protection**

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Full contact wears gloves from nitrile rubber material.
- Splash contact wears gloves from nitrile rubber material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter AX (EN 371).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

| | |
|---|---|
| Appearance: Form | Liquid |
| : Color | Colorless |
| Odour | Benzene like |
| Odour Threshold | Not Available |
| pH | Not Available |
| Melting point/range | Not Available |
| Boiling point/range | 40-60 °C |
| Flash point | <-21 °C (closed cup) |
| Evaporation rate | Not Available |
| Flammability (solid, gas) | Not Available |
| Explosion limits: lower | 0.8 %(V) |
| upper | 7.4 %(V) |
| Vapour Pressure | 350 hPa at 20°C |
| Relative vapour density | Not Available |
| Density | 0.645-0.665 g/ml at 20°C |
| Water solubility | 0.01 g/l at 20°C |
| Partition coefficient (n-octanol/water) | Not Available |
| Auto-Ignition temperature | 250 °C |
| Decomposition Temperature | Not Available |
| Viscosity | Not Available |
| Explosive properties | Not Explosive |
| Oxidizing properties | The substance or mixture is not classified as oxidizing |

SECTION 10: Stability and reactivity**10.1 Reactivity**

Highly flammable.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with strong oxidizing.

The substance can react dangerously with strong oxidizing agents.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents. Unsuitable working materials: Various plastics, rubber

10.6 Hazardous decomposition products

Carbon monoxides, Carbon dioxides, (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

LC₅₀ (inhalation, rat): >5 mg/l/ 4h.

LD₅₀ (dermal, rabbit): >2000 mg/kg.

LD₅₀ (oral, rat): >2000 mg/kg.

Acute oral toxicity

Symptoms: nausea.

Acute inhalation toxicity

Irritation symptoms in the respiratory tract, drowsiness.

Skin corrosion/irritation

Slight irritations. Degreasing effect on the skin, Danger of skin absorption.

Serious eye damage/eye irritation

Slight irritations.

Respiratory or skin sensitization

Not Available

Germ cell mutagenicity

Not Available

Carcinogenicity

Not Available

Reproductive toxicity

Animal experiments suggest that the substance may lead to an impairment of reproductive performance also man.

Teratogenicity

Not Available

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May cause pneumonia or chemical pneumonitis.

Further information

After accidental swallowing the substance may pose a risk of aspiration. Passage into the lung (vomiting) can result in a condition resembling pneumonia (chemical pneumonitis).

After absorption: Headache, dizziness, agitation, spasms, unconsciousness.

Cardiovascular failure and respiratory paralysis.

Damage of lungs.

The product should be handled with the care usual when dealing with chemicals.

SECTION 12: Ecological information

Mixture

12.1 Toxicity

Toxicity to daphnia and other aquatic invertebrates EC₅₀ Daphnia magna: 1.26-12.6 mg/l.

12.2 Persistence and degradability

Biodegradability Not Available

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water) Not Available

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Biological effects: toxic for aquatic organisms. May cause long term adverse effects in the aquatic environment. Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

| | |
|------------------------------|-------------------------------|
| UN Number | 1268 |
| UN proper shipping name | PETROLEUM DISTILLATES, N.O.S. |
| Transport hazard class(es) | 3 |
| Hazchem Code | 3YE |
| Packing group | II |
| Environmental hazards | Yes |
| Special precautions for user | Yes |

Sea transport (IMDG)

| | |
|------------------------------|-------------------------------|
| UN Number | 1268 |
| UN proper shipping name | PETROLEUM DISTILLATES, N.O.S. |
| Transport hazard class(es) | 3 |
| Packing group | II |
| Marine pollutant | Yes |
| Special precautions for user | Yes |
| EmS | F-E S- E |

Air transport (IATA)

| | |
|------------------------------|-------------------------------|
| UN Number | 1268 |
| UN proper shipping name | PETROLEUM DISTILLATES, N.O.S. |
| Transport hazard class(es) | 3 |
| Packing group | II |
| Environmental hazards | Yes |
| Special precautions for user | No |

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-------------------------------|---|
| Regulatory Information | Listed in the Australian Inventory of Chemical Substances (AICS). |
| Poisons Schedule | S5 |

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information**Full text of H-Statements referred to under sections 2 and 3**

| | |
|-------|---|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361f | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H411 | Toxic to aquatic life with long lasting effects. |

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

ChemSupply Australia Pty Ltd Ph. (08) 8440 2000.

Revision Date

01/06/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.